



CJM15G feeder illustrated

The New Generation® Series CJ Sunflower Feeder

Droll Yankees feeders can be disassembled for easy cleaning and part replacement.

Cleaning: *Please, for the sake of the birds, keep your feeders clean!* Dirty feeders can harm the birds. Use a mild soap & water solution and a soft brush for thorough, simple cleaning. Dry completely before filling with seed.

Disassemble

1. Remove the top cap by sliding the top cap halfway up the bail wire which will allow the top cap with the bail wire to fall to the side. Gently pull each end of the bail wire out of the bail rod.
2. Squeeze the tube, slightly oblong in shape, horizontal with the bail rod, and reach inside the tube and remove the bail rod.
3. Disassemble each pair of ports which are held together with a nut and a Phillips screw, keeping the Phillips screw in place on the port for reassembly.
Note: Removal of the lower pair of ports will release the base.

Assemble

1. Install the bail rod by squeezing the tube, slightly oblong in shape, horizontal with both holes which will accept the bail rod, and insert the bail rod into the holes in the tube.
2. Port Assembly – **Important: Replace the ports by starting at the top of the tube working your way down.** While the tube is in a horizontal position, hold a nut in place on a port without a Phillips screw with your finger, while placing the port onto the tube. The nut must be held in place on the port until secured by the Phillips screw. Take a port with the Phillips screw, and place opposite of the port with the nut and tighten the Phillips screw.
Note: Remember to place the base on the feeder before assembling the lower pair of ports.
3. Replace the top cap by inserting each end of the bail wire into the bail rod, and slide the top cap down into place on the tube.

